

(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

**EP 1 300 959 A1**

(12)

**EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
**09.04.2003 Bulletin 2003/15**

(51) Int Cl.7: **H04B 1/38, A45F 5/00**

(21) Application number: **02256619.4**

(22) Date of filing: **24.09.2002**

(84) Designated Contracting States:  
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR  
IE IT LI LU MC NL PT SE SK TR**  
Designated Extension States:  
**AL LT LV MK RO SI**

(72) Inventor: **Lehtonen, Jarmo**  
**20660 Littoinen (FI)**

(74) Representative: **Read, Matthew Charles et al**  
**Venner Shipley & Co.**  
**20 Little Britain**  
**London EC1A 7DH (GB)**

(30) Priority: **05.10.2001 US 970777**

(71) Applicant: **Nokia Corporation**  
**02150 Espoo (FI)**

**(54) Mobile phone strap holder apparatus and method**

(57) The invention involves a mobile phone (10) and strap apparatus (11) for carrying a mobile phone. A mobile phone (10) is provided with openings (12-14) in the corners of the mobile phone housing (15) through which a flexible line (20) is passed and cooperates with a strap (21) and latch (26) that secures ends of the flexible line

(20). The strap (21), latch (26) and flexible line (20) are adapted to secure an object between the mobile phone housing (15), the flexible line (20) and strap (21) when ends of the flexible line (20) are drawn through the latch (26).

**EP 1 300 959 A1**

**Description****FIELD**

[0001] This invention relates to carrying apparatus for a mobile device.

**BACKGROUND OF THE INVENTION**

[0002] Throughout the world users of mobile devices such as mobile phones have grown so attached to the use of their mobile phones that they attempt to carry them everywhere. This is not a difficult task in most working environments, when a simple belt mounted holster can carry the mobile phone. It is also common to secure a carrying strap to a single corner of the mobile phone housing to thereby allow the user of the phone to place the phone in a pocket or purse with the strap conveniently extending from the pocket or purse. Use of the phone simply requires the user to grip the single carrying strap and withdraw the phone from pocket or purse to either make or receive a call. In addition to mobile phone holsters, straps designed to wrap around the mobile device and around a portion of the body, have also developed. Some holster arrangements, as shown and described in U.S. Patent No. 5,586,704, issued to Alexander, et al. on December 24, 1996, provide a shoulder holster for carrying a portable telephone near the body of a user. The shoulder holster is provided with an opening into which the mobile phone may be placed. The holster itself is provided with a hook surface on the back of the holster that cooperates with a loop surface on a panel of the strap that passes over a shoulder, down a portion of the user's back and then around and underneath the arm pit of the user, where it is then secured to the strap panel. Similar approaches have been taken to strap a mobile phone in a holster strapped to a leg of a golfer as is shown in U.S. Design Patent D447,864 to Casparian, issued September 18, 2001.

[0003] As adequate as these just described approaches may be in the environments for which they were designed, major drawbacks arise in their use when these approaches are called upon to carry a mobile phone in environments where the user is highly active, such as hiking, running or golfing. In these instances the mobile phone user wants to secure the mobile phone to an arm, wrist, neck, a golf bag or on the body when the user is simply moving about.

[0004] The instant invention avoids the problems inherent in holster/carrying strap arrangements of the past. The invention is remarkably simple and exceedingly expeditious to use in a nearly universal manner in a host of environments where the mobile phone user desires quick and easy access to his/her phone.

**SUMMARY OF THE INVENTION**

[0005] The mobile phone and strap for the mobile

phone of the instant invention includes a mobile phone having a housing that includes at least two openings in the housing to accommodate a flexible line, for use with a strap adapted to accommodate the flexible line, when the line passes through one of the openings and a portion of the strap and then through another opening, whereupon the ends of the flexible line intersect one another before passing through another portion of the strap. A latch element is provided which is adapted to secure the ends of the flexible line such that an object disposed between the strap and the intersecting flexible line becomes secured between the mobile phone and strap, when ends of the flexible line are drawn through the latch element and a latch element secures the lines one to the other.

[0006] More specifically, the mobile phone housing includes at least four openings in the housing to accommodate a flexible line for use with a strap adapted to accommodate the flexible line when the line passes through one of the openings and a portion of the strap and then through another opening, whereupon the ends of the flexible line intersect one another before the ends of the line pass through other openings and another portion of the strap. A latch element is provided, which is adapted to secure the ends of the flexible line such that an object disposed between the strap and the intersecting flexible line becomes secured between the mobile phone and strap when ends of the flexible line are drawn through the latch element and a latch element secures the lines one to the other. In this preferred embodiment the four openings in the housing are disposed in regions remote from each other in an array in the housing to be proximate the corners of the mobile phone housing.

[0007] The invention further embraces a method of securing a mobile phone to an object. Specifically, the invention is comprised of the following steps.

[0008] First, providing a mobile phone housing that includes at least two openings in the housing.

[0009] Second, providing a flexible line.

[0010] Third, providing a strap that is adapted to provide a portion thereof that will accommodate the passage of the flexible line there through.

[0011] Fourth, providing a latch element that is adapted to secure the ends of the line when the ends of the line have passed through the latch element.

[0012] Fifth, passing an end of the flexible line through one of the openings and a portion of the strap and then through another opening.

[0013] Sixth, bringing ends of the line across each other in an intersecting manner and thereafter through the latch element.

[0014] Seventh, drawing the ends of the line through the latch element, such that an object disposed between the intersecting lines and strap thereby firmly secures the mobile phone to the object.

[0015] A primary advantage/objective of this invention resides in its effortless utility. It provides a mobile phone having a housing that functions not only to protect the

mobile phone while in active use but also provides a number of openings in the housing that allow the mobile phone to utilize a flexible line and a strap to secure the phone in a host of ways to objects, and individuals in a variety of physical locations.

[0016] Another advantage/object of the invention resides in the simple flexible line and strap and a latch mechanism that readily allows the mobile phone to be securely fastened in place on an object or person.

#### **BRIEF DESCRIPTION OF THE DRAWINGS**

[0017] The present invention is further described in the detailed description which follows in reference to the noted plurality of drawings by way of non-limiting examples of embodiments of the present invention in which like reference numerals represent similar parts throughout the several views of the drawings wherein:

FIG. 1 is a perspective view of a preferred embodiment of the invention;

FIG. 2 is a front view of an upper portion of a mobile phone as shown in FIG. 1;

FIG. 3 is an illustration of the invention in use on the neck and body of a person;

FIG. 4 is an illustration of the invention in use on the neck of a person;

FIG. 5 is an illustration of the invention in use on the arm of a person;

FIG. 6 is an illustration of the invention in use on the wrist of a person;

FIG. 7 is an illustration of the invention in use on a hiker's backpack strap;

FIG. 8 is an illustration of the invention in use in a draped fashion, secured to a belt disposed around a body of a person;

FIG. 9 is an illustration of the invention in use by a jogger; and;

FIG. 10 is an illustration of the invention in use on an object such as a golf bag.

#### **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT**

[0018] Reference is now made to FIG. 1 which illustrates a preferred embodiment of the invention in which the backside of a mobile phone 10 is shown. The mobile phone 10 has a housing 15 which is provided with four corner openings 12, 13, 14 (FIG. 2) and a corner opening not shown in the drawing but identical to the opening 13 but hidden from view in the other corner and therefore not visible in this illustration. A flexible line 20 is shown passing through the corner openings 12, 13, 14 and the corner opening not shown as noted above. A strap holder 11, indicated by lead line and arrowhead, is positioned as shown near the backside of the mobile phone 10.

[0019] It will be observed that flexible line 20 has a

pair of ends 20a, 20b that will be observed to pass through a latch 26, that includes a latch release button 27. If one will visually trace the flexible line 20, it will be seen that the flexible line 20 passes through one of the corner openings 14 (FIG. 1) and a portion 22 of the strap 21 and then through the corner opening 12, whereupon the line 20 is brought together and they intersect one another at the location indicated by reference arrow 23. The ends 20a, 20b of the line 20 then pass through the corner opening 13 and the corner opening not shown. The ends 20a, 20b of the line 20 then are passed through a strap portion 24 as is shown and then through the latch 26.

[0020] It is to be understood that when the latch 26 is held secure by a hand not shown and when the latch release button is depressed the ends 20a, 20b may be grasped by another hand and pulled so as to draw the line 20 through the latch and object (not shown) that is disposed between the strap 21 and the intersecting line 20, drawing the ends of the line 20a, 20b through the latch 26, will secure an object between the mobile phone 10 and the strap holder 11.

[0021] In FIG. 1 no object has been shown between the mobile phone 10 and the strap holder 11 as the physical presence of such an object between the mobile phone 10 and strap 21 in FIG. 1 would obscure the cooperation of the flexible line 20 and strap holder 11 as well as the corner openings 12, 13 and 14.

[0022] Attention now is directed to FIGS. 3 through 10 which illustrate the multifaceted utility of this simple invention.

[0023] FIG. 3 depicts a mobile phone 10 secured by flexible line 20 which passes around the neck and body of person 30. FIG. 4 shows the mobile phone 10 supported by the flexible line 20 as the line 20 passes around a neck of the person 30. The mobile phone 10 may be suspended by either of its corner openings as is indicated by the arrows 32, 33 which are intended to suggest that the mobile phone 10 may be reversed in its position.

[0024] FIG. 5 shows a mobile phone 10 secured to an arm 34 whereas FIG. 6 has the mobile phone 10 secured to a wrist 35.

[0025] FIG. 7 is intended to convey an action figure 40 such as a hiker or backpacker with the mobile phone 10 secured to a backpack harness strap 41.

[0026] FIG. 8 depicts a partial section of a human figure 45 with a body strap 46 onto which has been secured the mobile phone 10. FIG. 9 shows yet another action figure 50 jogging with the mobile phone positioned as shown on the belt 51.

[0027] In FIG. 3 to FIG. 9 the invention has been employed to secure a mobile phone 10 to various portions of a human anatomy. FIG. 10 is intended to convey yet another useful manner of employing the invention where the object to which the mobile phone 10 is secured is a golf bag 52.

[0028] In a most complete sense the invention in-

cludes the following steps for securing a mobile phone to an object.

- providing a mobile phone housing that includes at least four openings in the housing;
- providing a flexible line;
- providing a strap that is adapted to provide at least two portions thereof that will accommodate the passage of the flexible line there through;
- providing a latch element that is adapted to secure the ends of the line when the ends of the line have passed through the latch element;
- passing an end of the flexible line through one of the openings and a portion of the strap and then through another opening.
- bringing ends of the line across each other in an intersecting manner and thereafter through first one of the other openings whereas the other end of the line passes through the remaining opening and then through the other portion of the strap and thereafter through latch element, and then;
- drawing the ends of the line through the latch element, such that an object disposed between the intersecting lines and strap thereby firmly secures the mobile phone to the object.

[0029] Although the present invention has been described herein with reference to a particular method, materials and embodiments, the present invention is not intended to be limited to the particulars disclosed herein. Rather, the present invention extends to all functionally equivalent structures, methods and use, such as are within the scope of the appended claims. Thus, the invention may be used with devices that function as mobile telecommunications apparatus with internet browsers or other data communication facilities, and the term mobile phone is to be construed accordingly.

#### Claims

1. A mobile phone and strap holder for the mobile phone, the mobile phone and strap holder comprising:

a mobile phone having a housing that includes at least two openings in the housing to accommodate a flexible line for use with a strap adapted to accommodate the flexible line when the line passes through one of the openings and a portion of the strap and then through another opening whereupon the ends of the flexible line intersect one another before passing through another portion of the strap, whereupon a latch element is adapted to secure the ends of the flexible line such that an object disposed between the strap and the intersecting flexible line becomes secured between the mobile phone

and strap when ends of the flexible line are drawn through the latch element and a latch element secures the lines one to the other.

2. The mobile phone and strap holder of claim 1 or 2 wherein the openings in the housing are disposed in regions of the housing remote from each other.
3. The mobile phone and strap holder of claim 1 wherein the mobile phone housing includes at least four openings.
4. The mobile phone and strap holder of claim 3 wherein the four openings in the housing are disposed in regions remote from each other in an array in the housing to be proximate corners of the mobile phone housing.
5. A mobile phone and strap holder for the mobile phone, the mobile phone and strap holder comprising:

a mobile phone having a housing that includes at least four openings in the housing to accommodate a flexible line for use with a strap adapted to accommodate a flexible line when the line passes through one of the openings and a portion of the strap and then through another opening whereupon the ends of the flexible line intersect one another before the ends of the line pass through other openings and another portion of the strap, whereupon a latch element is adapted to secure the ends of the flexible line such that an object disposed between the strap and the intersecting flexible line becomes secured between the mobile phone and strap when ends of the flexible line are drawn through the latch element and a latch element secures the lines one to the other.

6. The mobile phone and strap holder of claim 5 wherein the four openings in the housing are disposed in regions remote from each other in an array in the housing to be proximate corners of the mobile phone housing.
7. A method of securing a mobile phone to an object comprising the following steps:

- (a) providing a mobile phone housing that includes at least two openings in the housing,
- (b) providing a flexible line,
- (c) providing a strap that is adapted to provide a portion thereof that will accommodate the passage of the flexible line there through,
- (d) providing a latch element that is adapted to secure ends of the line when the ends of the line have passed through the latch element

- (e) passing an end of the flexible line through one of the openings and a portion of the strap and then through another opening,
- (f) bringing ends of the line across each other in an intersecting manner and thereafter through the latch element, and then 5
- (g) drawing the ends of the line through the latch element, such that an object disposed between the intersecting lines and strap thereby firmly secures the mobile phone to the object. 10
8. A method of securing a mobile phone to an object comprising the following steps:
- (a) providing a mobile phone housing that includes at least four openings in the housing, 15
- (b) providing a flexible line,
- (c) providing a strap that is adapted to provide at least two portions thereof that will accommodate the passage of the flexible line there through, 20
- (d) providing a latch element that is adapted to secure the ends of the line when the ends of the line have passed through the latch element
- (e) passing an end of the flexible line through one of the openings and a portion of the strap and then through another opening, 25
- (f) bringing ends of the line across each other in an intersecting manner and thereafter through first one of the other openings whereas the other end of the line passes through the remaining opening and then through the other portion of the strap and there after through latch element, and then 30
- (g) drawing the ends of the line through the latch element, such that an object disposed between the intersecting lines and strap thereby firmly secures the mobile phone to the object. 35
9. A configuration according to any one of claims 1 to 8 and including said flexible line 40

45

50

55





FIG. 3




FIG. 4




FIG. 5





FIG. 6






FIG. 8




FIG. 7




FIG. 10




FIG. 9



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 02 25 6619

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	GB 2 266 452 A (NOKIA MOBILE PHONES LTD) 3 November 1993 (1993-11-03) * page 4, line 16 - page 7, line 3 *	1	H04B1/38 A45F5/00
A	US 6 094 566 A (EMMERT STEVEN CLARK ET AL) 25 July 2000 (2000-07-25) * column 1, line 58 - column 4, line 45 *	1	
A	WO 99 56448 A (MICHALERIS MICHALIS) 4 November 1999 (1999-11-04) * page 9, line 16-31 *	1	
A	DE 198 33 517 A (FABRA VERTRIEBSGESELLSCHAFT MB) 27 January 2000 (2000-01-27) * column 4, line 14-44 *	1,5,7,8	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			H04B A45F H04M
The present search report has been drawn up for all claims			
Place of search: <b>MUNICH</b>		Date of completion of the search: <b>3 January 2003</b>	Examiner: <b>Koob, M</b>
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure F : intermediate document			

EP 0 FORM 1503 (3.92) (P04/2001)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 02 25 6619

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

03-01-2003

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
GB 2266452	A	03-11-1993	FI	90614 B	30-11-1993
US 6094566	A	25-07-2000	NONE		
WO 9956448	A	04-11-1999	GR	1003029 B	10-12-1998
			EP	0992148 A1	12-04-2000
			WO	9956448 A1	04-11-1999
DE 19833517	A	27-01-2000	DE	19833517 A1	27-01-2000

EP FORM P-03

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82